D-Link DGS-1210-28P Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U





Marke : D-Link

Artikel-Code: DGS-1210-28P/E

Produktname : DGS-1210-28P

24x 10/100/1000BASE-T PoE RJ-45, 4x 100/1000 Mbps combo, 56 Gbps, 41.7 Mpps, 8K MAC, 440 x 250 x 44 mm
D-Link DGS-1210-28P. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 28. Vollduplex. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 56 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE). Rack-Einbau, Formfaktor: 1U

Management-Funktionen	
Switch-Typ *	Managed
Switch-Ebene	L2
Quality of Service (QoS) Support	✔

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	28
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Anzahl Gigabit Ethernet (Kupfer) Anschlüsse	24
Menge SFP-Modul-Steckplätze	4

Netzwerk	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
Port-Spiegelung	✔
Vollduplex	✔
Unterstützung Datenflusssteuerung	✔
Link Aggregation	✔
Spannbaum-Protokoll	✔
Anzahl der VLANs	4094

Datenübertragung	
Routing-/Switching-Kapazität *	56 Gbit/s
MAC-Adressentabelle *	16000 Eintragungen

Sicherheit	
DHCP-Funktionen	DHCP server, DHCP client
Zugriffkontrollliste	✔
IGMP-Snooping	✔
MAC Adressen Filtern	✔
SSH-/SSL-Unterstützung	✔

Design	
Rack-Einbau *	✔
Stapelbar *	✘
Formfaktor	1U
Anzahl Lüfter	3 Lüfter

Energie	
Stromverbrauch (Standardbetrieb)	238,4 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔

Betriebsbedingungen	
Betriebstemperatur	-5 - 50 °C
Temperaturbereich bei Lagerung	-20 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%

Gewicht und Abmessungen	
Breite	440 mm
Tiefe	250 mm
Höhe	44 mm
Gewicht	3,7 kg

Verpackungsdaten	
Verpackungsbreite	365 mm
Verpackungstiefe	521 mm
Verpackungshöhe	92 mm
Paketgewicht	4,93 kg

Zertifikate	
Zertifizierung	FCC Class A CE Class A ICES-003 VCCI Class A C-Tick BSMI



0790069467783



790069467783



0790069399671



790069399671

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date