TP-Link Omada EAP653 WLAN Access Point 2976 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link **Produktfamilie:** Omada **Artikel-Code:** EAP653

Produktname : EAP653

TP-Link Omada EAP653. 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 2976 Mbit/s. Unterstützte Sicherheitsalgorithmen: HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA, WPA2, WPA3. Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß

Merkmale	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Maximale Datenübertragungsrate *	2976 Mbit/s
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s
Maximale Datenübertragungsrate (5 GHz)	2402 Mbit/s
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
Frequenzband	2.4 - 5 GHz
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11h
Verkabelungstechnologie	10/100/1000Base-T(X)
Zahl der Benutzer	250 Benutzer
Automatische Kanalwahl	✔
Automatischer Kanalscan	✔
MIMO	✔
MIMO-Typ	Multi User MIMO
Spread-Spectrum Methode	OFDMA
AP-Modus-Eigenschaften anpassen	Vernetzung von Netzen
VLAN-Unterstützung	✔
Ratenbeschränkung	✔
Unterstützung Datenflusssteuerung	✔
Bandsteuerung	✔
Airtime Fairness (ATF)	✔
Quality of Service (QoS) Support	✔
BeamForming	✔
Sendeleistung (CE)	27 dbm
Sendeleistung (FCC)	22 dbm
Sicherheit	
Unterstützte Sicherheitsalgorithmen *	HTTPS, SNMP, SNMPv2, SNMPv3, SSH, WPA, WPA2, WPA3

Sicherheit	
MAC Adressen Filtern	✔
Management-Funktionen	
Web-basiertes Management	✔
Syslog	✔
Upgradefähige Firmware	✔
Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Gleichstrom-Anschluss (DC)	✔
Energie	
Power over Ethernet (PoE) *	✔
DC Spannungsrange	12 V
Design	
Platzierung *	Zimmerdecke, Wand
Produktfarbe *	Weiß
Reset-Knopf	✔
LED-Anzeigen	✔
Antenne	
Antennentyp *	Intern
Gewicht und Abmessungen	
Breite	160 mm
Tiefe	160 mm
Höhe	33,6 mm
Verpackungsdaten	
Verpackungsart	Box
Lieferumfang	
Menge pro Packung	1 Stück(e)
Montageset	✔
Schnellstartübersicht	✔
Betriebsbedingungen	
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Luftfeuchtigkeit bei Lagerung	5 - 90%

4897098685235

4897098685242

0840030705236

840030705236

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date