TP-Link Omada SG3452XP Netzwerk-Switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Schwarz

Marke : TP-Link **Produktfamilie:** Omada **Artikel-Code:** SG3452XP

Produktname : SG3452XP



TP-Link Omada SG3452XP. Switch-Typ: Managed, Switch-Ebene: L2+. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 48, Konsolen-Port: RJ-45/Micro-USB. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 176 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE.... Netzstecker: AC-Eingangsbuchse. Power over Ethernet (PoE). Rack-Einbau, Formfaktor: 1U

Management-Funktionen	
Switch-Typ *	Managed
Switch-Ebene	L2+
Quality of Service (QoS) Support	✔
Web-basiertes Management	✔
Cloud-verwaltet	✔
ARP-Inspektion	✔
Konfiguration der Standorteinstellungen (CLI)	✔
Systemereignisprotokoll	✔

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	48
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Menge Modul-Steckplätze SFP+	4
Konsolen-Port	RJ-45/Micro-USB
Netzstecker	AC-Eingangsbuchse

Netzwerk	
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z
10G-Unterstützung *	✔
Port-Spiegelung	✔
Unterstützung Datenflusssteuerung	✔
Link Aggregation	✔
Broadcast-Sturmkontrolle	✔
Ratenbeschränkung	✔
Spannbaum-Protokoll	✔
Head-of-Line (HOL)-Blocking	✔
VLAN-Unterstützung	✔

Datenübertragung	
Routing-/Switching-Kapazität *	176 Gbit/s
Transferrate	130,9 Mpps
MAC-Adressentabelle *	16000 Eintragungen
Store-and-Forward	✔
Jumbo Frames Unterstützung	✔

Sicherheit	
SSH-/SSL-Unterstützung	✔
BPDU-Filterung/Schutz	✔
IP-MAC-Portbindung	✔
Authentifizierung	Auto VLAN, Gast VLAN

Multicast-Funktionen	
Multicast Unterstützung	✔

Design	
Rack-Einbau *	✔
Formfaktor	1U
Produktfarbe	Schwarz
Reset-Knopf	✔
LED-Anzeigen	✔
Anzahl Lüfter	3 Lüfter

Energie	
Energiequelle *	AC
Netzteil enthalten *	✔
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50/60 Hz
Stromverbrauch (max.)	635,7 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Anzahl Power over Ethernet plus (PoE+) Anschlüsse	48
Power over Ethernet (PoE) Leistung pro Anschluss	30 W
Gesamtleistung Power over Ethernet (PoE)	500 W

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Luftfeuchtigkeit bei Lagerung	5 - 90%
Wärmeableitung	2169,2 BTU/h

Gewicht und Abmessungen	
Breite	440 mm
Tiefe	330 mm

Datenübertragung	
Jumbo-Frames	9000
Datenpaket-Pufferspeicher	12 MB

Sicherheit	
DHCP-Funktionen	DHCP client, DHCP relay, DHCP server
Zugriffkontrollliste	✔
IGMP-Snooping	✔
MAC Adressen Filtern	✔
Statische Anschlusssicherheit	✔

Gewicht und Abmessungen	
Höhe	44 mm

Lieferumfang	
Mitgelieferte Kabel	AC
Schnellstartübersicht	✔

Zertifikate	
Zertifizierung	CE, FCC, RoHS

6935364006495

1210002611657

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date