TP-Link Omada EAP625GP-WALL WLAN Access Point 1201 Mbit/s Weiß Power over Ethernet (PoE)



Marke : TP-Link **Produktfamilie:** Omada **Artikel-Code:** EAP625GP-WALL

Produktname : EAP625GP-WALL

GPON, RJ-45, Wi-Fi 6, SC-APC

TP-Link Omada EAP625GP-WALL WLAN Access Point 1201 Mbit/s Weiß Power over Ethernet (PoE):

Komplette Omada-Lösung für optische Netzwerke
Die Omada-Lösung für optische Netzwerke bietet GPON in Unternehmensqualität. Sie integriert nahtlos wichtige Komponenten wie Omada-Switches, Gateways, OLTs (Optische Leitungsterminals) und ONUs (Optische Netzwerkeinheiten) – ideal für PtMP-Umgebungen (Point-to-Multipoint) wie Hotels und Mehrfamilienhäuser.



Eine Glasfaser, mehrere Dienste
Verbinden Sie eine Glasfaser mit dem EAP625GP-Wall, um Kameras, PCs und Fernseher anzuschließen und Daten-, Sprach-, kabelgebundene und kabellose Internet-, HD-Video- sowie VoIP-Dienste bereitzustellen.

Nahtlose Wi-Fi 6 Mesh-Netzwerke
Nutzten Sie die GPON Wi-Fi 6-Technologie für ein robustes und nahtloses Netzwerkerlebnis mit Geschwindigkeiten von bis zu 1,8 Gbit/s.
Omada Mesh und 802.11k/v Roaming sorgen für eine durchgängig stabile und zuverlässige Verbindung.

Merkmale	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Maximale Datenübertragungsrate *	1201 Mbit/s
Frequenzband	2.4 - 5 GHz
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Abgedeckter Bereich	50 m²
Zahl der Benutzer	120 Benutzer
VLAN-Unterstützung	✔
Ratenbeschränkung	✔
Kabellose Verdrahtung	✔
Bandsteuerung	✔
Airtime Fairness (ATF)	✔
Quality of Service (QoS) Support	✔

Sicherheit	
Unterstützte Sicherheitsalgorithmen *	WPA, WPA2, WPA3
MAC Adressen Filtern	✔
Funktionen Service Set Identifier (SSID)	Multiple SSIDs, SSID broadcast, SSID-Übertragung ein/aus
Anzahl der SSID-Unterstützung	16

Management-Funktionen	
Web-basiertes Management	✔

Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	2

Energie	
Power over Ethernet (PoE) *	✔
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50/60 Hz

Design	
Platzierung *	Wand
Produktfarbe *	Weiß
Reset-Knopf	✔

Gewicht und Abmessungen	
Breite	143 mm
Tiefe	86 mm
Höhe	44,6 mm
Gewicht	350 g

Betriebsbedingungen	
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C

Betriebsbedingungen	
Luftfeuchtigkeit bei Lagerung	5 - 90%

1210002607841

8885020625080

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date