Intellinet 561808 Netzwerk-Switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE)





Marke : Intellinet

Artikel-Code: 561808

Produktname : 561808

Intellinet 561808. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 5. Vollduplex. MAC-Adressentabelle: 2048 Eintragungen, Routing-/Switching-Kapazität: 10 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE). Wandmontage

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	5
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)

Netzwerk	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x
10G-Unterstützung *	✗
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T
unterstütze Kabeltypen	Cat3, Cat5, Cat5e
Vollduplex	✓
Unterstützung Datenflusssteuerung	✓

Datenübertragung	
Routing-/Switching-Kapazität *	10 Gbit/s
MAC-Adressentabelle *	2048 Eintragungen
Store-and-Forward	✓
Jumbo Frames Unterstützung	✓
Paketweiterleitungsrate (1 Gbit/s)	1488000 pps
Paketweiterleitungsrate (100 Mbit/s)	148800 pps
Paketweiterleitungsrate (10 Mbit/s)	14880 pps
Datenpaket-Pufferspeicher	1 MB

Design	
Gehäusematerial	Metall
LED-Anzeigen	Aktivität, Link, PoE, Leistung
Wandmontage	✓

Energie	
Energiequelle *	AC
Netzteil enthalten *	✓
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50 - 60 Hz
Stromverbrauch (max.)	72 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✓
Gesamtleistung Power over Ethernet (PoE)	65 W

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	0 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 90%

Gewicht und Abmessungen	
Breite	168 mm
Tiefe	93 mm
Höhe	32 mm
Gewicht	400 g

Lieferumfang	
Mitgelieferte Kabel	AC
Betriebsanleitung	✓

Verpackungsdaten	
Paketgewicht	900 g

Zertifikate	
Konformitätsbescheinigungen	CE, RoHS, Eidgenössische Kommunikationskommission (FCC)
Zertifizierung	FCC Class A, CE, RoHS, UKCA, NDAA



0766623561808



766623561808

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date