CyberPower BPE72V60ART2U Batterieerweiterungsmodul Tower/Rack 2U, PP45 Anschluss (1), 72Vdc, 9Ah/12V* 12, integriertem Ladegerät, komp. mit OL2000ERTXL2U/OL2200ERTXL2U, OL3000ERTXL2U inkl. 19" Railkit



Marke : CyberPower

Artikel-Code: BPE72V60ART2U

Produktname : BPE72V60ART2U Batterieerweiterungsmodul Tower/Rack 2U, PP45 Anschluss (1), 72Vdc, 9Ah/12V* 12, integriertem Ladegerät, komp. mit OL2000ERTXL2U/OL2200ERTXL2U, OL3000ERTXL2U inkl. 19" Railkit

BPE72V60ART2U Batterieerweiterungsmodul Tower/Rack 2U, PP45 Anschluss (1), 72Vdc, 9Ah/12V* 12, integriertem Ladegerät, komp. mit OL2000ERTXL2U/OL2200ERTXL2U, OL3000ERTXL2U inkl. 19" Railkit

CyberPower BPE72V60ART2U Batterieerweiterungsmodul Tower/Rack 2U, PP45 Anschluss (1), 72Vdc, 9Ah/12V* 12, integriertem Ladegerät, komp. mit OL2000ERTXL2U/OL2200ERTXL2U, OL3000ERTXL2U inkl. 19" Railkit:

CyberPower BPE72V60ART2U ist eine externe Batterieerweiterung (EBM), die in Verbindung mit kompatiblen USV-Systemen verwendet werden kann, um eine längere Systemlaufzeit bei Stromunterbrechung zu gewährleisten. Das Batteriemodul verfügt über DC-Plug-and-Play-Stromanschlüsse zum Hinzufügen mehrerer EBMs.

Das Produkt verfügt über Hot-Swap-fähige Akkupacks, mit denen Benutzer das Batteriemodul sicher austauschen können, ohne die angeschlossenen Verbraucher zu unterbrechen. Die im EBM verwendete versiegelte Bleibatterie ist wartungsfrei und sicher, was die zuverlässige Leistung des Stromsystems gewährleistet. Das Produkt ist mit einem Metallgehäuse in Industriequalität ausgestattet und eignet sich für Rechenzentren und kritische Anwendungen.

Merkmale	
Akku-/Batteriespannung *	12 V
Batteriekapazität *	9 Ah
Anzahl enthaltener Akkus/Batterien *	6 Stück(e)
Produktfarbe	Schwarz
Hot-Swap-Batterie	✔
Akkuladezeit	4 h
Kompatibilität	OL2000ERTXL2U OL2200ERTXL2U OL3000ERTXL2U

Akku/Batterie	
Akku-/Batterietechnologie *	Plombierte Bleisäure (VRLA)

Gewicht und Abmessungen	
Gewicht	44 kg
Breite	433 mm
Höhe	88 mm
Tiefe	600 mm

Verpackungsdaten	
Verpackungsbreite	565 mm

Verpackungsdaten	
Verpackungshöhe	240 mm
Verpackungstiefe	880 mm
Paketgewicht	52,7 kg
Verpackungsgewicht	52,7 kg

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 45 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 90%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m

Logistikdaten	
Warentarifnummer (HS)	8504909000
Ursprungsland	China

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date