CyberPower CP1600EIPFCRM2U Unterbrechungsfreie Stromversorgung (USV) Line-Interaktiv 1,6 kVA 1000 W 8 AC-Ausgänge



Marke : CyberPower **Artikel-Code:** CP1600EIPFCRM2U

Produktname : CP1600EIPFCRM2U

- Line-interactive USV Topologie
- Energiesparende Technologie
- Versorgung mit reiner Sinuswelle
- Automatische Spannungsregulierung (AVR)
- Überlastschutz
- Kritische / nicht kritische Ausgänge
- Hot-Swap-fähige Batterien
- LCD-Farbdisplay
- LED-Statusanzeige
- USB-Kommunikationsanschluss
- Hochgeschwindigkeits-Ethernet-Datenübertragung
- Gehäuse mit kurzer Bautiefe
- PowerPanel Verwaltungssoftware
- SNMP / HTTP-Fernverwaltungsfähigkeit (optional)
- Überspannungs- und Blitzschutz
- EMI und RFI Filte



1600 VA, 1000 W, LCD, Line-interaktive, IEC C13 x 8, 169 - 271 VAC, 433 x 86 x 274 mm

Merkmale	
USV-Topologie *	Line-Interaktiv
Ausgangskapazität *	1,6 kVA
Ausgangsleistung *	1000 W
Wellenform *	Reiner Sinus
Eingangs-Betriebsspannung (min) *	169 V
Eingangs-Betriebsspannung (max) *	271 V
Eingangsfrequenz *	50/60 Hz
Output Frequenz	50/60 Hz
Regulierung der Ausgangsfrequenz	1 Hz
Automatische Spannungsregulierung	✔
Wärmeableitung	20,5 BTU/h
Leistungsfaktor	0,625
Leistungsfaktorkorrekturfilter (PFC)	Aktiv
ECO-Modus	✔
EMI/RFI Lautstärkefilter	✔
Druckanstiegsschutz	✔
Energieschutzeigenschaften	Überspannung, Überlastschutz
Energiequelle	AC
Herausnehmbarer Stromkabel	✔

Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler
Stecker	C14-Koppler
Anzahl der AC-Ausgänge	8 AC-Ausgänge
USB Anschluss	✔
Anzahl USB 2.0 Anschlüsse	1
USB-Port-Typ	USB Typ-B
Serielle Schnittstelle	✔

Anschlüsse und Schnittstellen	
RS-232 port	1
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	2

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Anzahl unterstützter Akkus/Batterien	1
Typische Backup-Zeit bei voller Belastung	2,5 min
Typische Backup-Zeit bei halber Belastung	10,4 min
Hot-Swap-Batterie	✔

Design	
Formfaktor *	Rackmount
Gehäusematerial	Metall
Rack-Kapazität	2U
Kühlung	Aktiv
Eingebauter Ventilator	✔
Produktfarbe *	Schwarz
Steuerung	Tasten
Display-Typ	LCD
LED-Anzeigen	✔

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%

Zertifikate	
Konformitätsbescheinigungen	CE, RoHS

Anschlüsse und Schnittstellen	
Serielle Schnittstelle	RS-232
Anzahl serielle Anschlüsse	1

Gewicht und Abmessungen	
Breite	433 mm
Tiefe	274 mm
Höhe	86 mm
Gewicht	20,5 kg

Sonstige Funktionen	
Akku-/Batterietyp	RBP0166

4711027798240

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date