ZYXEL

Zyxel BE22000 22000 Mbit/s Weiß Power over Ethernet (PoE)

Marke : Zyxel

Artikel-Code: WBE665S-EU0102F

Produktname : BE22000

Zyxel BE22000. 2,4 GHz, 5 GHz, 6 GHz, Maximale Datenübertragungsrate: 22000 Mbit/s, Ethernet LAN Datentransferraten: 1000,2500,10000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß





Merkmale	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✔
Maximale Datenübertragungsrate *	22000 Mbit/s
Maximale Datenübertragungsrate (2,4 GHz)	1376 Mbit/s
Maximale Datenübertragungsrate (5 GHz)	8646 Mbit/s
Maximale Datenübertragungsrate (6 GHz)	11530 Mbit/s
Ethernet LAN Datentransferraten	1000,2500,10000 Mbit/s
Netzstandard	IEEE 802.11be, IEEE 802.11ax, IEEE 802.11ac, IEEE 802.11h, IEEE 802.11g, IEEE 802.11a, IEEE 802.11b
MIMO	✔
MIMO-Typ	Multi User MIMO
WLAN-Multimedia (WMM)/(WME)	✔
Schnelles Roaming	✔
VLAN-Unterstützung	✔
Kabellose Verdrahtung	✔
Bandsteuerung	✔
Zellulärer Koexistenzfilter (CCF)	✔
Empfängersensitivität	-104 dBm

Sicherheit	
Automatisches kabelloses Verteilersystem (WDS)	✔
Fernauthentifizierungs-Einwähl-Benutzerdienst (RADIUS)	✔

Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Gleichstrom-Anschluss (DC)	✔

Energie	
Power over Ethernet (PoE) *	✔
DC Spannungsrange	24 - 48 V

Design	
Produktfarbe *	Weiß
Internationale Schutzart (IP-Code)	IP67

Antenne	
Antennentyp *	Intern
Antenne Zunahmeniveau (max)	6 dBi

Zertifikate	
Zertifizierung	ETSI EN 300 328 ETSI EN 301 893 ETSI EN 303 687 EN 301 489-1 EN 301 489-17 EN55032 EN55035 EN61000-3-2/-3 EN60601-1-2 EN 62368-1 IEC 62368-1

Gewicht und Abmessungen	
Breite	410 mm
Tiefe	410 mm
Höhe	110 mm
Gewicht	4,96 kg

Verpackungsdaten	
Verpackungsbreite	564,5 mm
Verpackungstiefe	535,5 mm
Verpackungshöhe	176,5 mm

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date

Management-Funktionen	
Kommandozeilen-Schnittstelle (CLI)	✔
Zugangspunktmanagement	L2-isolation, MAC filtering, Rogue AP detection
Cloud-verwaltet	✔
Upgradefähige Firmware	✔

Verpackungsdaten	
Paketgewicht	8,1 kg

Lieferumfang	
Menge pro Packung	1 Stück(e)
Montageset	✔

Betriebsbedingungen	
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Betriebstemperatur	-40 - 70 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Luftfeuchtigkeit bei Lagerung	10 - 90%

4718937651474

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date