FUJITSU PRIMERGY

Fujitsu PRIMERGY RX2540 M6 Server Rack (2U) Intel® Xeon® Gold 6334 3,6 GHz 32 GB DDR4-SDRAM 900 W



Marke : Fujitsu

Produktfamilie: PRIMERGY

Artikel-Code: VFY:R2546SC160IN

Produktname : RX2540 M6

Fujitsu PRIMERGY RX2540 M6. Prozessorfamilie: Intel® Xeon® Gold, Prozessor-Taktfrequenz: 3,6 GHz, Prozessor: 6334. Speicherkapazität: 32 GB, Interner Speichertyp: DDR4-SDRAM. HDD Schnittstelle: SATA III, Serial Attached SCSI (SAS). Ethernet/LAN, Verkabelungstechnologie: 10/100/1000Base-T(X). Optisches Laufwerk - Typ: DVD±RW. Stromversorgung: 900 W, Unterstützung für redundantes Netzteil. Gehäusetyp: Rack (2U)

Prozessor	
Prozessorhersteller *	Intel
Prozessorfamilie *	Intel® Xeon® Gold
Prozessor *	6334
Prozessor-Taktfrequenz *	3,6 GHz
Prozessor Boost-Frequenz	3,7 GHz
Anzahl Prozessorkerne	8
Prozessor-Cache	18 MB
Motherboard Chipsatz	Intel C621A

Speicher	
Speicherkapazität *	32 GB
Interner Speichertyp *	DDR4-SDRAM
Speicherkartensteckplätze	32x DIMM
ECC	✔
Speichertaktfrequenz	3200 MHz
RAM-Speicher maximal *	12 TB

Speichermedium	
HDD Schnittstelle	SATA III, Serial Attached SCSI (SAS)
Maximale unterstützte Anzahl der HDD	16
Unterstützte Hard-Disk Drive Größen	2.5"
RAID-Unterstützung *	✔
Hot-Plug-Unterstützung	✔
Optisches Laufwerk - Typ *	DVD±RW

Netzwerk	
Ethernet/LAN	✔
Verkabelungstechnologie	10/100/1000Base-T(X)

Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	5
Anzahl USB 2.0 Anschlüsse	6
Anzahl VGA (D-Sub) Anschlüsse	2

Erweiterungssteckplätze	
PCI-Express x8-Slots	3
PCI-Express x16-Slots	4

Design	
Gehäusetyp *	Rack (2U)
Produktfarbe	Schwarz, Edelstahl
Rack-Einbau	✔
Ungenutzter Lüfter-Support	✔
Bezel	✔

Leistungen	
BIOS-Typ	UEFI
Trusted Platform Module (TPM)	✔
Trusted Platform Module (TPM) Version	2.0

Energie	
Unterstützung für redundantes Netzteil *	✔
Stromversorgung *	900 W
Anzahl der unterstützten redundanten Stromversorgungen	2
Stromversorgung - Eingang Spannung	100-240 V
Stromversorgung - Eingangsfrequenz	50/60 Hz

Betriebsbedingungen	
Betriebstemperatur	0 - 35 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 85%

Gewicht und Abmessungen	
Breite	482,5 mm
Tiefe	800 mm
Höhe	86,9 mm

4065221736875

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 16-SEP-2026. Prints or copies of Information are only valid on the printed Publication date