APC Rack PDU 2G, mit Messfunktion über Ausgang mit Schaltung, Null HE, 32 A, 230 V, (21) C13 & (3) C19



Marke : APC

Artikel-Code: AP8653

Produktname : Rack PDU 2G, mit Messfunktion über Ausgang mit Schaltung, Null HE, 32 A, 230 V, (21) C13 & (3) C19

Rack PDU 2G, mit Messfunktion über Ausgang mit Schaltung, Null HE, 32 A, 230 V, (21) C13 & (3) C19 APC Rack PDU 2G, mit Messfunktion über Ausgang mit Schaltung, Null HE, 32 A, 230 V, (21) C13 & (3) C19. PDU-Typen: Messgerät, pro Steckdose abgerechnet, Geändert, Rack-Kapazität: 0U, Typ: Einphasig. Anzahl der AC-Ausgänge: 24 AC-Ausgänge, AC-Steckertypen: C13-Koppler, C19-Koppler, Stecker: IEC309. Kabellänge: 3 m. Überwachung: Strom, Leistung, Spannung, Ausgabekontrolle: Aussperrung, Recyceln, Ausstellen, Anmachen. Nominale Eingang Spannung: 230 V, Stromstärke (maximal): 32 A, AC Eingangsfrequenz: 50 - 60 Hz

Design	
PDU-Typen *	Messgerät, pro Steckdose abgerechnet, Geändert
Typ	Einphasig
Rack-Kapazität *	0U
Montage	Senkrecht
Produktfarbe	Schwarz
Anschlüsse und Schnittstellen	
Anzahl der AC-Ausgänge *	24 AC-Ausgänge
Stecker	IEC309
AC-Steckertypen *	C13-Koppler, C19-Koppler
Merkmale	
Kabellänge	3 m
Management-Funktionen	
Überwachung	Strom, Leistung, Spannung
Ausgabekontrolle	Aussperrung, Recyceln, Ausstellen, Anmachen
Energie	
Nominale Eingang Spannung *	230 V
AC Eingangsfrequenz	50 - 60 Hz
Stromstärke (maximal) *	32 A
Nominale Ausgang Spannung	230 V
Ladekapazität	7680 VA
Maximaler Eingang Strom pro Phase	32 A
Maximale Gesamtstromaufnahme pro Phase	32 A
Energieschutzeigenschaften	Überlastschutz
Max. Leistung	7680 W

Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, VDE
Betriebsbedingungen	
Betriebstemperatur	-5 - 45 °C
Temperaturbereich bei Lagerung	-25 - 65 °C
Relative Luftfeuchtigkeit in Betrieb	5 - 95%
Luftfeuchtigkeit bei Lagerung	5 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m
Gewicht und Abmessungen	
Breite	56 mm
Tiefe	51 mm
Höhe	1829 mm
Gewicht	8,23 kg
Verpackungsdaten	
Paketgewicht	10,5 kg
Verpackungsbreite	162 mm
Verpackungstiefe	118 mm
Verpackungshöhe	2038 mm
Logistikdaten	
Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	8595,81

0731304276982

731304276982

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-OCT-2026. Prints or copies of Information are only valid on the printed Publication date