Cudy GS1028PS2 Netzwerk-Switch Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz







Marke : Cudy

Artikel-Code: GS1028PS2

Produktname : GS1028PS2

- 24× GbE mit 802.3at/af PoE
- 2× Uplink GbE + 2× Uplink Combo
- 300-W-Netzteil
- Erweiterung Ein/Aus, VLAN Ein/Aus
- Überwachungsfunktion Ein/Aus
- PoE Max, PoE pro Port LED
- Intelligente Lüfterkühlung
- Desktop, Rackmontage
- 440×220×44 mm (17.32×8.66×1.73")

24-Port Gigabit PoE+ Switch with 2 Gigabit SFP Ports
Cudy GS1028PS2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24. MAC-Adressentabelle: 8192 Eintragungen, Routing-/Switching-Kapazität: 52 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Netzstecker: AC-Eingangsbuchse. Power over Ethernet (PoE). Rack-Einbau

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Menge SFP-Modul-Steckplätze	2
Optischer Kabelverbinder	SFP
Netzstecker	AC-Eingangsbuchse

Netzwerk	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G-Unterstützung *	✗
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-X
unterstütze Kabeltypen	Cat3, Cat5, Cat5e

Datenübertragung	
Routing-/Switching-Kapazität *	52 Gbit/s
Transferrate	38,68 Mpps
MAC-Adressentabelle *	8192 Eintragungen
Store-and-Forward	✓

Design	
Rack-Einbau *	✓
Produktfarbe	Schwarz
Gehäusematerial	Metall
Anzahl Lüfter	2 Lüfter

Energie	
Energiequelle *	AC

Energie	
Netzteil enthalten *	✓
AC Eingangsspannung	90 - 260 V
AC Eingangsfrequenz	50/60 Hz

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✓
Anzahl Power over Ethernet plus (PoE+) Anschlüsse	24
Power over Ethernet (PoE) Leistung pro Anschluss	30 W
Gesamtleistung Power over Ethernet (PoE)	300 W

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Luftfeuchtigkeit bei Lagerung	10 - 95%

Gewicht und Abmessungen	
Breite	440 mm
Tiefe	204 mm
Höhe	44 mm
Gewicht	2,9 kg

Verpackungsdaten	
Paketgewicht	3,46 kg

6971690790981

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date