ZYXEL

Zyxel NWA90AX PRO 2400 Mbit/s Weiß Power over Ethernet (PoE)

Marke : Zyxel

Artikel-Code: NWA90AXPRO-EU0102F

Produktname : NWA90AX PRO



Zyxel NWA90AX PRO. 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 2400 Mbit/s. Unterstützte Sicherheitsalgorithmen: 802.1x RADIUS, EAP, WEP, WPA, WPA2, WPA2-Enterprise, WPA2-PSK, WPA3. Ethernet LAN Datentransferraten: 1000,2500 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß



Merkmale	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Maximale Datenübertragungsrate *	2400 Mbit/s
Maximale Datenübertragungsrate (2,4 GHz)	575 Mbit/s
Maximale Datenübertragungsrate (5 GHz)	2400 Mbit/s
Ethernet LAN Datentransferraten	1000,2500 Mbit/s
Netzstandard	IEEE 802.11n, IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g
MIMO	✔
MIMO-Typ	Multi User MIMO
WLAN-Multimedia (WMM)/(WME)	✔
VLAN-Unterstützung	✔

Sicherheit	
Unterstützte Sicherheitsalgorithmen *	802.1x RADIUS, EAP, WEP, WPA, WPA2, WPA2-Enterprise, WPA2-PSK, WPA3
MAC Adressen Filtern	✔

Protokolle	
Management-Protokolle	SNMP

Management-Funktionen	
Web-basiertes Management	✔
Upgradefähige Firmware	✔

Energie	
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50/60 Hz
Eingangsstrom	0.3 A
Ausgangsspannung	12 V
Ausgangsstrom	2 A

Design	
Platzierung *	Zimmerdecke
Produktfarbe *	Weiß
LED-Anzeigen	✔

Antenne	
Antennentyp *	Intern
Antennenfunktionen	Integrierte Antenne
Antenne Zunahmeniveau (max)	4 dBi

Gewicht und Abmessungen	
Breite	140 mm
Tiefe	140 mm
Höhe	37,5 mm
Gewicht	352 g

Verpackungsdaten	
Verpackungsbreite	240 mm
Verpackungstiefe	155 mm
Verpackungshöhe	60 mm
Paketgewicht	668 g

Betriebsbedingungen	
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Betriebstemperatur	0 - 50 °C

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date

Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Gleichstrom-Anschluss (DC)	✔

Energie	
Power over Ethernet (PoE) *	✔

Betriebsbedingungen	
Temperaturbereich bei Lagerung	-40 - 70 °C
Luftfeuchtigkeit bei Lagerung	10 - 90%

4718937630592

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date