# ASUS Prime MR120 Fan ARGB Reverse White Computergehäuse Ventilator 12 cm Weiß





**Marke :** ASUS **Artikel-Code:** 90DA00L3-B09000

**Produktname :** Prime MR120 Fan ARGB Reverse White

- Extra dicker 28-mm-Lüfterrahmen für ideale Kühlleistung
- Leiser Betrieb mit bis zu 23 dB(A)
- 20 adressierbare RGB-LEDs mit einem kreisförmigen Design, das das System beleuchtet
- Beidseitige Rahmenbeleuchtung sorgt für eine nahtlose und lebendige Lichtästhetik
- PWM-Steuerung mit einer Lüfterdrehzahl von bis zu 1600 U/min sorgt für optimale Kühlung bei einer Vielzahl von Arbeitsbelastungen
- Aura Sync-Kompatibilität ermöglicht koordinierte Lichtfarben und -effekte über eine Reihe von Geräten hinweg
- Erhältlich in Schwarz oder Weiß und in Standard- oder umgekehrter Ausrichtung, um eine Vielzahl von PC-Konstruktionen zu ermöglichen

Prime MR120 White ARGB Reverse-Gehäuselüfter Single (beidseitige Beleuchtung, 20 adressierbare RGB-LEDs, 28 mm Rahmen, PWM-Steuerung, Lüfterdrehzahl 1600 U/min, 23dB(A) Lärmpegel, 58 CFM, Weiß)

ASUS Prime MR120 Fan ARGB Reverse White Computergehäuse Ventilator 12 cm Weiß:

Der ASUS Prime MR120 ARGB Reverse-Lüfter mit beidseitiger Beleuchtung am Rahmen und 28 mm Dicke bietet eine ideale Kühlleistung

| Leistungen | |
|---|---|
| Empfohlene Platzierung * | Computergehäuse |
| Typ * | Ventilator |
| Lüfterdurchmesser | 12 cm |
| Unterstützung der Pulsweitenmodulation | ✔ |
| Lagertyp | Gleitlager |
| Ventilatoren Geschwindigkeit (max) | 1600 RPM |

| Design | |
|---|---|
| Produktfarbe * | Weiß |
| Anzahl Lüfter | 1 Lüfter |
| Beleuchtungs-LED | ✔ |
| Anzahl der LEDs | 20 |
| Farben der Beleuchtung | Multi |
| Displaytyp | Nicht zutreffend |

| Energie | |
|---|---|
| Startspannung | 6 V |
| Stromverbrauch Lüfter | 2,16 W |
| Ventilatoren Spannung | 12 V |
| Ventilatoren Strom | 0,18 A |

| Gewicht und Abmessungen | |
|---|---|
| Höhe | 120 mm |
| Gewicht | 179 g |
| Abmessungen Gebläse (B x T x H) | 120 x 120 x 28 mm |
| Verpackungsbreite | 123 mm |
| Verpackungstiefe | 36 mm |
| Verpackungshöhe | 142 mm |
| Paketgewicht | 200 g |

| Sonstige Funktionen | |
|---|---|
| Lüfterleistung | 58 cfm |
| Luftdruck | 1,38 mmH2O |
| Geräuschpegel | 23 dB |

4711636046084

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date