ASUS ROG Strix Aiolos SSD-Gehäuse Schwarz M.2

Marke : ASUS

Artikel-Code: 90DD02U0-MA9000

Produktname : ROG Strix Aiolos



- Rasend schneller USB-C® 3.2 Gen 2×2 für Übertragungsgeschwindigkeiten von bis zu 20 Gbit/s
- Die Flüssigsilikon-Gummibeschichtung bietet eine elegante, hitzebeständige Oberfläche und hält Staub fern, um die Langlebigkeit des Geräts zu gewährleisten
- Das interne Wärmeleitpad leitet die Wärme effektiv ab und sorgt so für eine stabile Leistung und eine längere Lebensdauer der SSD
- Duale M.2-Schnittstelle unterstützt M.2 NVMe® PCIe® und SATA SSDs (2242/2260/2280)
- Werkzeugfreies Design mit Push-to-Open-Mechanismus für schnellen SSD-Einbau oder -Ausbau
- Das exklusive ROG SSD Dashboard bietet Echtzeitüberwachung über eine benutzerdefinierte UI und sorgt für eine schnellere und zuverlässigere SSD-Leistung
- Exklusiver Metallhaken mit Stoffanhänger für Nutzer unterwegs

ROG Strix Aiolos USB-C 3.2 Gen 2x2 SSD-Gehäuse (duale M.2 NVMe PCIe- und SATA-Unterstützung, werkzeugfreie Installation, SSD Dashboard für den Gerätestatus, Kühlsystem mit Wärmeleitpad)



Speichermedium	
Anzahl der unterstützten Speicherlaufwerke *	1
Größe des Speicherlaufwerks *	M.2
Unterstützte Speicherlaufwerk-Schnittstellen *	PCI Express, SATA
Unterstütze Datenträgerhöhe	22 mm
Unterstützte Speicherlaufwerkslängen	80,60,42 mm
NVMe	✔

Anschlüsse und Schnittstellen	
USB Anschluss *	✔
USB-Version	USB 3.2 Gen 2x2
USB-Stecker	USB Typ-C

Design	
Produkttyp *	SSD-Gehäuse
Produktfarbe *	Schwarz

Leistungen	
Datenübertragungsrate	20 Gbit/s

Energie	
Eingangsspannung	5 V

Systemanforderung	
Unterstützt Windows-Betriebssysteme	Windows 10, Windows 11
Unterstützt Mac-Betriebssysteme	Mac OS X 15.0 Sequoia

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-40 - 60 °C
Relative Luftfeuchtigkeit in Betrieb	15 - 90%
Luftfeuchtigkeit bei Lagerung	10 - 90%

Gewicht und Abmessungen	
Breite	46 mm
Tiefe	115,5 mm
Höhe	15,1 mm
Gewicht	139 g
Verpackungsbreite	165 mm
Verpackungstiefe	110 mm
Verpackungshöhe	44 mm
Paketgewicht	374 g

Lieferumfang	
Mitgelieferte Kabel	USB Typ-C auf USB Typ-C
Betriebsanleitung	✔

4711636342087

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date