ZYXEL

Zyxel GS1200-8V3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grau



Marke : Zyxel

Artikel-Code: GS1200-8V3-EU0101F

Produktname : GS1200-8V3



Zyxel GS1200-8V3. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. Vollduplex. MAC-Adressentabelle: 4000 Eintragungen, Routing-/Switching-Kapazität: 16 Gbit/s. Netzstandard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE.... Netzstecker: DC-Anschluss. Formfaktor: Desktop

Management-Funktionen	
Switch-Typ *	Managed
Switch-Ebene	L2
Quality of Service (QoS) Support	✔
Web-basiertes Management	✔

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	8
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Netzstecker	DC-Anschluss

Netzwerk	
Netzstandard *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G-Unterstützung *	✘
Kupfer Ethernet Verkabelungstechnologie	10BASE-T, 100BASE-T, 1000BASE-T
Port-Spiegelung	✔
Vollduplex	✔
Unterstützung Datenflusssteuerung	✔
Broadcast-Sturmkontrolle	✔
VLAN-Unterstützung	✔
Virtuelle LAN-Funktionen	Port-based VLAN

Datenübertragung	
Routing-/Switching-Kapazität *	16 Gbit/s
Transferrate	11,9 Mpps
MAC-Adressentabelle *	4000 Eintragungen
Jumbo Frames Unterstützung	✔
Jumbo-Frames	15
Datenpaket-Pufferspeicher	0,192 MB

Sicherheit	
DHCP-Funktionen	DHCP client
IGMP-Snooping	✔
Passwortschutz	✔
Warteschleifenplanungs-Algorithmen	Weighted Round Robin (WRR)

Multicast-Funktionen	
Multicast Unterstützung	✔
Anzahl der gefilterten Multicast-Gruppen	128

Design	
Rack-Einbau *	✘
Stapelbar *	✘
Formfaktor	Desktop
Produktfarbe	Grau
LED-Anzeigen	✔

Leistungen	
Ventilatorlos	✔
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1266805 h

Energie	
Energiequelle *	AC
Netzteil enthalten *	✔
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50/60 Hz
Stromverbrauch (max.)	3,81 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✘

Betriebsbedingungen	
Betriebstemperatur	0 - 50 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Luftfeuchtigkeit bei Lagerung	10 - 95%
Wärmeableitung	13 BTU/h

Gewicht und Abmessungen	
Breite	193 mm
Tiefe	85 mm
Höhe	26 mm
Gewicht	268 g

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date

Zertifikate	
Zertifizierung	CE-LVD, BSMI CE, EAC, FCC, BSMI Class B

4718937649945

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date