D-Link 8-Port Multi-Gigabit Unmanaged PoE Switch





Marke : D-Link

Artikel-Code: DMS-108P/E

Produktname : 8-Port Multi-Gigabit Unmanaged PoE Switch

8 x 10/100Mbps/1G/2.5G PoE, 40 Gbps, 29.76 Mpps, 190 x 120 x 38 mm, 0.753 Kg
D-Link 8-Port Multi-Gigabit Unmanaged PoE Switch. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: 2.5G Ethernet (100/1000/2500), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 8. MAC-Adressentabelle: 4000 Eintragungen, Routing-/Switching-Kapazität: 40 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u,.... DC input Spannung: 54 V. Netzstecker: DC-Anschluss. Power over Ethernet (PoE)

Management-Funktionen	
Switch-Typ *	Unmanaged
Quality of Service (QoS) Support	✔
Traffic-Klassifizierung	✔

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	8
Basic Switching RJ-45 Ethernet Ports-Typ *	2.5G Ethernet (100/1000/2500)
Netzstecker	DC-Anschluss

Netzwerk	
Netzstandard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x
10G-Unterstützung *	✘
Auto MDI/MDI-X	✔
Ethernet LAN Datentransferraten	10,100,1000,2500 Mbit/s

Datenübertragung	
Routing-/Switching-Kapazität *	40 Gbit/s
Transferrate	29,76 Mpps
MAC-Adressentabelle *	4000 Eintragungen
Store-and-Forward	✔

Design	
Stapelbar *	✔
Produktfarbe	Schwarz
LED-Anzeigen	✔

Leistungen	
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	140688261 h

Energie	
Energiequelle *	Gleichstrom
Netzteil enthalten *	✔
DC input Spannung	54 V
Eingangsstrom	4.62 A
Stromverbrauch (max.)	261,02 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Anzahl Power over Ethernet (PoE) Anschlüsse	8
Power over Ethernet (PoE) Leistung pro Anschluss	90 W
Gesamtleistung Power over Ethernet (PoE)	290 W

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-10 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Luftfeuchtigkeit bei Lagerung	5 - 90%
Wärmeableitung	890,6 BTU/h

Gewicht und Abmessungen	
Breite	190 mm
Tiefe	120 mm
Höhe	38 mm
Gewicht	753 g

Zertifikate	
Zertifizierung	CB; UL; LVD; FCC; VCCI; IC; BSMI

790069476839

0790069476839

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date