ZYXEL

Zyxel GS1920-24HPV2 Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz

Marke : Zyxel

Artikel-Code: GS192024HPV2-EU0101F

Produktname : GS1920-24HPV2



Zyxel GS1920-24HPV2. Switch-Typ: Managed. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 56 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Power over Ethernet (PoE). Rack-Einbau



Management-Funktionen	
Switch-Typ *	Managed
Quality of Service (QoS) Support	✔
ARP-Inspektion	✔
Systemereignisprotokoll	✔
MIB Unterstützung	RFC 1066, RFC 1213, RFC 1157, RFC 1493, RFC 1643, RFC 1757, RFC 2011.2012,2013, RFC 2233, RFC 2358, RFC 2674, RFC 2819,2925, RFC 3621, RFC 4022, RFC 4113, RFC 4292, RFC 4293

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Anzahl Combo-SPF-Anschlüsse	4
Optischer Kabelverbinder	SFP

Netzwerk	
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G-Unterstützung *	✘
Kupfer Ethernet Verkabelungstechnologie	100BASE-TX, 1000BASE-T
Unterstützung Datenflusssteuerung	✔
Ratenbeschränkung	✔
Spannbaum-Protokoll	✔

Design	
Rack-Einbau *	✔
Produktfarbe	Schwarz
LED-Anzeigen	✔
Sicherheit	LVD, BSMI
Elektromagnetische Verträglichkeit	FCC 15 A, CE A, BSMI EMC

Leistungen	
Speicherkapazität	256 MB
Flash-Speicher	32 MB
Geräuschpegel	27,2 dB
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	638691 h

Energie	
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50 - 60 Hz
Stromverbrauch (max.)	463,5 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Anzahl Power over Ethernet (PoE) Anschlüsse	24
Gesamtleistung Power over Ethernet (PoE)	375 W

Betriebsbedingungen	
Betriebstemperatur	0 - 50 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Luftfeuchtigkeit bei Lagerung	10 - 95%
Wärmeableitung	1580,54 BTU/h

Netzwerk	
VLAN-Unterstützung	✔
Virtuelle LAN-Funktionen	Private VLAN, Voice VLAN, Protocol-based VLAN, MAC address-based VLAN, Port-based VLAN, IP subnet–based VLAN

Lichtwellenleiter	
Ethernet-Kabel Verkablungstechnologie	1000BASE-X

Datenübertragung	
Routing-/Switching-Kapazität *	56 Gbit/s
Transferrate	42 Mpps
MAC-Adressentabelle *	16000 Eintragungen
Datenpaket-Pufferspeicher	1,5 MB

Sicherheit	
DHCP-Funktionen	DHCP snooping, DHCP relay, DHCPv6 relay, DHCP client
Zugriffkontrollliste	✔
IGMP-Snooping	✔
Unterstützte Sicherheitsalgorithmen	802.1x RADIUS, SNMP, SNMPv3
MAC Adressen Filtern	✔
IP-MAC-Portbindung	✔
Authentifizierung	Gast VLAN, Port-basierte Authentifizierung
Passwortschutz	✔
Autentifizierungstyp	IEEE 802.1x, RADIUS
CPU-Verteidigung	✔
Warteschleifenplanungs-Algorithmen	SPQ, WFQ, Weighted Round Robin (WRR)

Multicast-Funktionen	
Multicast Unterstützung	✔

Gewicht und Abmessungen	
Breite	441 mm
Tiefe	270 mm
Höhe	44 mm
Gewicht	3,8 kg

Lieferumfang	
Mitgelieferte Kabel	AC
Rackmontageset	✔

Verpackungsdaten	
Verpackungsbreite	616 mm
Verpackungstiefe	355 mm
Verpackungshöhe	107 mm
Paketgewicht	4,97 kg

Zertifikate	
Zertifizierung	RoHS

Logistikdaten	
Warentarifnummer (HS)	85176990

4718937601936

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date