ZYXEL

Zyxel XGS2220-30HP Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Schwarz

Marke : Zyxel

Artikel-Code: XGS2220-30HP-EU0101F

Produktname : XGS2220-30HP



30-Port Layer3 Access Switch, 400W PoE (16xPoE+/10xPoE++), 24x1G RJ45, 2x10MultiGig RJ45, 4x10G SFP+ Uplink, inkl. 1 Jahr NebulaFlex Pro
Zyxel XGS2220-30HP. Switch-Typ: Managed, Switch-Ebene: L3. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24, Anzahl installierte SFP Module: 4. MAC-Adressentabelle: 32000 Eintragungen, Routing-/Switching-Kapazität: 168 Gbit/s. Netzstandard: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af,.... Power over Ethernet (PoE). Rack-Einbau



Management-Funktionen	
Switch-Typ *	Managed
Switch-Ebene	L3
Quality of Service (QoS) Support	✔
Web-basiertes Management	✔
Cloud-verwaltet	✔
ARP-Inspektion	✔

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Anzahl 10G Ethernet (Kupfer)-Ports	2
Anzahl installierte SFP Module *	4

Netzwerk	
Netzstandard *	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3x, IEEE 802.3z
10G-Unterstützung *	✔
Routing Eingänge	64

Datenübertragung	
Routing-/Switching-Kapazität *	168 Gbit/s
Transferrate	125 Mpps
MAC-Adressentabelle *	32000 Eintragungen
Statische Route	✔
Jumbo Frames Unterstützung	✔

Design	
Rack-Einbau *	✔
Produktfarbe	Schwarz
LED-Anzeigen	✔

Leistungen	
Speicherkapazität	1024 MB
Flash-Speicher	64 MB
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	268,305 h

Energie	
Energiequelle *	AC
Netzteil enthalten *	✔
AC Eingangsspannung	100 - 240 V
AC Eingangsfrequenz	50 - 60 Hz
Stromverbrauch (max.)	477 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Anzahl Power over Ethernet (PoE) Anschlüsse	26
Gesamtleistung Power over Ethernet (PoE)	400 W

Betriebsbedingungen	
Betriebstemperatur	-20 - 50 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Luftfeuchtigkeit bei Lagerung	10 - 90%
Wärmeableitung	1626,57 BTU/h

Datenübertragung	
Datenpaket-Pufferspeicher	2 MB

Sicherheit	
DHCP-Funktionen	DHCP relay, DHCP server
IGMP-Snooping	✔
IGMP-Proxy	✔
Unterstützte Sicherheitsalgorithmen	SNMP, SNMPv2, SNMPv3
BPDU-Filterung/Schutz	✔
Autentifizierungstyp	IEEE 802.1x, RADIUS, TACACS+

Multicast-Funktionen	
Multicast Unterstützung	✔
Multicast Listener Discovery (MLD) Snooping	MLD v1/v2

Protokolle	
GARP VLAN Registration Protocol (GVRP)	✔

Gewicht und Abmessungen	
Breite	441 mm
Tiefe	330 mm
Höhe	44 mm
Gewicht	4,35 kg

Verpackungsdaten	
Verpackungsbreite	580 mm
Verpackungstiefe	503 mm
Verpackungshöhe	95 mm
Paketgewicht	5,77 kg

Zertifikate	
Konformitätsbescheinigungen	RoHS, Eidgenössische Kommunikationskommission (FCC), Niederspannungsrichtlinie (LVD), CE

4718937625055

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date