NETGEAR

NETGEAR GS724TPP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grau



Marke : NETGEAR

Artikel-Code: GS724TPP-300EUS

Produktname : GS724TPP



NETGEAR GS724TPP. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24, Anzahl installierten SFP Module: 2. Routing-/Switching-Kapazität: 52 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Power over Ethernet (PoE). Rack-Einbau

Management-Funktionen	
Switch-Typ *	Managed
Switch-Ebene	L2
Web-basiertes Management	✔
Cloud-verwaltet	✔

Anschlüsse und Schnittstellen	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)
Anzahl installierten SFP Module *	2
Optischer Kabelverbinder	SFP

Netzwerk	
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x
VLAN-Unterstützung	✔
Anzahl der VLANs	256

Datenübertragung	
Routing-/Switching-Kapazität *	52 Gbit/s
Datenpaket-Pufferspeicher	1,5 MB

Sicherheit	
DHCP-Funktionen	DHCP client, DHCP snooping
Zugriffkontrollliste	✔
Zugriffskontrollliste (ACL) IPv4-Einträge	100
IGMP-Snooping	✔

Multicast-Funktionen	
Multicast Unterstützung	✔
Anzahl der gefilterten Multicast-Gruppen	512

Design	
Rack-Einbau *	✔
Produktfarbe	Grau
LED-Anzeigen	Aktivität, Link, PoE, Leistung, Geschwindigkeit, Ja
Ungenutzter Lüfter-Support	✔
Anzahl Lüfter	2 Lüfter

Leistungen	
Eingebauter Prozessor	✔
Prozessorhersteller	ARM
Prozessor	ARM Cortex-A55
Prozessortaktfrequenz	800 MHz
Speicherkapazität	512 MB
Flash-Speicher	64 MB
Geräuschpegel	26,1 dB
Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1784610 h

Energie	
Netzteil enthalten *	✔
Stromverbrauch (Standardbetrieb)	11,3 W
Stromverbrauch (max.)	20,69 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Anzahl Power over Ethernet plus (PoE+) Anschlüsse	24
Power over Ethernet (PoE) Leistung pro Anschluss	190 W
Gesamtleistung Power over Ethernet (PoE)	231,07 W

Betriebsbedingungen	
Betriebstemperatur	0 - 50 °C
Temperaturbereich bei Lagerung	-20 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%

Gewicht und Abmessungen	
Breite	440 mm
Tiefe	257 mm
Höhe	43,2 mm
Gewicht	3,15 kg



0606449162769



606449162769

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date