APC Smart-UPS SMT2200RMI2UC – 8x C13, 1x C19, USB, Rack-montierbar, SmartConnect, 2200VA





Marke : APC

Artikel-Code: SMT2200RMI2UC

Produktname : APC Smart-UPS SMT2200RMI2UC – 8x C13, 1x C19, USB, Rack-montierbar, SmartConnect, 2200VA

APC Smart-UPS SMT2200RMI2UC – 8x C13, 1x C19, USB, Rack-montierbar, SmartConnect, 2200VA
APC Smart-UPS SMT2200RMI2UC – 8x C13, 1x C19, USB, Rack-montierbar, SmartConnect, 2200VA. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 2,2 kVA, Ausgangsleistung: 1980 W. AC-Steckertypen: C13-Koppler, C19-Koppler, Anzahl der AC-Ausgänge: 9 AC-Ausgänge, USB-Port-Typ: USB Typ-A. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Batterielebensdauer (max.): 5 Jahr(e), Akkuladezeit: 3 h. Formfaktor: Rackmount, Produktfarbe: Schwarz, Metallisch, Rack-Kapazität: 2U. Konformitätsbescheinigungen: RoHS, Zertifizierung: CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Merkmale	
USV-Topologie *	Line-Interaktiv
Ausgangskapazität *	2,2 kVA
Ausgangsleistung *	1980 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	151 V
Eingangs-Betriebsspannung (max) *	302 V
Eingangsfrequenz *	50/60 Hz
Ausgangs-Betriebsspannung (min)	220 V
Ausgangs-Betriebsspannung (max)	240 V
Anstieg der Energiemenge	375 J
Reaktionszeit	6 ms
Ausgangsspannung Gesamtverzerrungsfaktor THD	5%
Geräuschpegel	55 dB
Energieschutzeigenschaften	Überspannung
Akustische Signale	✔
Akustische Alarm-Modi	Alarm bei Batteriebetrieb, Warnung bei geringer Batterie

Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler, C19-Koppler
Anzahl der AC-Ausgänge	9 AC-Ausgänge
Anzahl der Output IEC Jumper	3
USB Anschluss	✔
Anzahl USB 2.0 Anschlüsse	1
USB-Port-Typ	USB Typ-A
Serielle Schnittstelle	✔
Serielle Schnittstelle	RJ-45
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1
SmartSlot	✔
SmartConnect-Anschluss	✔

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Anzahl unterstützter Akkus/Batterien	1
Batterielebensdauer (max.)	5 Jahr(e)
Akkuladezeit	3 h
Batteriepatrone Wechsel	RBC43

Design	
Formfaktor *	Rackmount
Rack-Kapazität	2U
Kabellänge	2 m
Produktfarbe *	Schwarz, Metallisch
Displaytyp	LCD

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 45 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 3000 m
Höhe bei Lagerung	0 - 15000 m

Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE

Lieferumfang	
Rackmontageset	✔
Mitgelieferte Kabel	RS-232, USB-Kabel
Management-Karte enthalten	✘

Nachhaltigkeit	
Nachhaltigkeitszertifikate	Green Premium

Gewicht und Abmessungen	
Breite	432 mm
Tiefe	683 mm
Höhe	86 mm
Gewicht	42,3 kg

Verpackungsdaten	
Software-CD	✔
Verpackungsbreite	600 mm
Verpackungstiefe	980 mm
Verpackungshöhe	254 mm
Paketgewicht	49,7 kg

Logistikdaten	
Produkte pro Palette	8 Stück(e)
Warentarifnummer (HS)	85078000

Logistikdaten	
Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	3416,11



0731304337324



731304337324

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date