APC BV800I-GR Unterbrechungsfreie Stromversorgung (USV) Line-Interaktiv 0,8 kVA 450 W 4 AC-Ausgänge



Marke : APC

Artikel-Code: BV800I-GR

Produktname : BV800I-GR

APC BV800I-GR. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 0,8 kVA, Ausgangsleistung: 450 W. AC-Steckertypen: Typ F, Anzahl der AC-Ausgänge: 4 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Batteriekapazität: 7 Ah, Akku-/Batteriespannung: 12 V. Formfaktor: Kompakt, Produktfarbe: Schwarz, Kabellänge: 1,52 m. Konformitätsbescheinigungen: RoHS, Zertifizierung: CE REACH



Merkmale	
USV-Topologie *	Line-Interaktiv
Ausgangskapazität *	0,8 kVA
Ausgangsleistung *	450 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	170 V
Eingangs-Betriebsspannung (max) *	280 V
Eingangsfrequenz *	50/60 Hz
Output Frequenz	50/60 Hz
Automatische Spannungsregulierung	✔
Anstieg der Energiemenge	156 J
Übertragungszeit (Line-Modus in Batterie-Modus)	6 ms
Anzahl der Eingangs-Phasen	1
Anzahl der Ausgangs-Phasen	1
Geräuschpegel	40 dB
Druckanstiegsschutz	✔
Akustische Signale	✔
Akustische Alarm-Modi	Alarm bei Batteriebetrieb, Warnung bei geringer Batterie, Überlastungsalarm

Anschlüsse und Schnittstellen	
AC-Steckertypen	Typ F
Anzahl der AC-Ausgänge	4 AC-Ausgänge
SmartSlot	✘
SmartConnect-Anschluss	✘

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Batteriekapazität	7 Ah
Akku-/Batteriespannung	12 V

Akku/Batterie	
Akkuladezeit	8 h
Kaltstart	✔

Design	
Formfaktor *	Kompakt
Kabellänge	1,52 m
Produktfarbe *	Schwarz
LED-Anzeigen	✔

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 90%
Höhe bei Betrieb	0 - 1968,3 m

Zertifikate	
Konformitätsbescheinigungen	RoHS
Zertifizierung	CE REACH

Lieferumfang	
Management-Karte enthalten	✘

Gewicht und Abmessungen	
Breite	160 mm
Tiefe	305 mm
Höhe	92 mm
Gewicht	5,3 kg

Verpackungsdaten	
Verpackungsbreite	373 mm
Verpackungstiefe	143 mm
Verpackungshöhe	237 mm
Paketgewicht	5,6 kg

Logistikdaten	
Warentarifnummer (HS)	85078000

Sonstige Funktionen	
Nominale Ausgang Spannung	230 V

0731304338369

731304338369

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date