APC Smart-UPS Li-ion SCL500RMI1UNC USV – 4x C13, kurze Tiefe, Rack-/Tower-/Wandmontage, NMC, 500VA

Marke : APC

Artikel-Code: SCL500RMI1UNC



Produktname : APC Smart-UPS Li-ion SCL500RMI1UNC USV – 4x C13, kurze Tiefe, Rack-/Tower-/Wandmontage, NMC, 500VA

- 500 VA/400 W Line-Interactive-USV mit reiner Sinuswelle, 1 HE, für Rackmontage
- Ideal für kleine Edge-Umgebungen, Backoffice, Netzwerkinfrastruktur und IDF/MDF-Schränke
- Lithium-Ionen-Akku minimiert den Bedarf an Akkuwechseln während der Lebensdauer der USV
- Kurze USV-Tiefe bietet zusätzlichen Platz für Kabelmanagement
- Vorinstallierte Netzwerkmanagementkarte für netzwerkbasierte USV-Überwachung und -Verwaltung

APC Smart-UPS Li-ion SCL500RMI1UNC USV – 4x C13, kurze Tiefe, Rack-/Tower-/Wandmontage, NMC, 500VA

APC Smart-UPS Li-ion SCL500RMI1UNC USV – 4x C13, kurze Tiefe, Rack-/Tower-/Wandmontage, NMC, 500VA. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 0,5 kVA, Ausgangsleistung: 400 W. AC-Steckertypen: C13-Koppler, Anzahl der AC-Ausgänge: 4 AC-Ausgänge. Akku-/Batterietechnologie: Lithium-Ion (Li-Ion). Formfaktor: Rackmount/Tower, Produktfarbe: Grau, Rack-Kapazität: 1U. Nachhaltigkeitszertifikate: Green Premium



Merkmale	
USV-Topologie *	Line-Interaktiv
Ausgangskapazität *	0,5 kVA
Ausgangsleistung *	400 W
Wellenform *	Reiner Sinus
Eingangs-Betriebsspannung (min) *	208 V
Eingangs-Betriebsspannung (max) *	253 V
Eingangsfrequenz *	47/63 Hz
Ausgangs-Betriebsspannung (min)	230 V
Ausgangs-Betriebsspannung (max)	230 V

Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler
Anzahl der AC-Ausgänge	4 AC-Ausgänge
SmartSlot	✗
SmartConnect-Anschluss	✗

Akku/Batterie	
Akku-/Batterietechnologie	Lithium-Ion (Li-Ion)

Design	
Formfaktor *	Rackmount/Tower
Rack-Kapazität	1U
Produktfarbe *	Grau

Lieferumfang	
Rackmontageset	✔
Management-Karte enthalten	✔

Nachhaltigkeit	
Nachhaltigkeitszertifikate	Green Premium

Gewicht und Abmessungen	
Breite	432 mm
Tiefe	232 mm
Höhe	44 mm
Gewicht	4,2 kg

Logistikdaten	
Warentarifnummer (HS)	85078000
Gesamter Kohlendioxid-Fußabdruck (kg of CO2e)	602,99



0731304402565



731304402565

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date