APC SRTG6KXLI Unterbrechungsfreie Stromversorgung (USV) Doppelwandler (Online) 6 kVA 6000 W 3 AC-Ausgänge



Marke : APC

Artikel-Code: SRTG6KXLI

Produktname : SRTG6KXLI

APC SRTG6KXLI. USV-Topologie: Doppelwandler (Online), Ausgangskapazität: 6 kVA, Ausgangsleistung: 6000 W. AC-Steckertypen: C13-Koppler, C19-Koppler, Anzahl der AC-Ausgänge: 3 AC-Ausgänge. Akku-/Batterietechnologie: Plombierte Bleisäure (VRLA), Akku-/Batteriespannung: 96 V, Batterielebensdauer (max.): 5 Jahr(e). Formfaktor: Kompakt, Produktfarbe: Schwarz, Displaytyp: LCD. Zertifizierung: CE, EN/IEC 62040-1



Merkmale	
USV-Topologie *	Doppelwandler (Online)
Ausgangskapazität *	6 kVA
Ausgangsleistung *	6000 W
Wellenform *	Sine
Eingangs-Betriebsspannung (min) *	100 V
Eingangs-Betriebsspannung (max) *	285 V
Eingangsfrequenz *	40/70 Hz
Ausgangs-Betriebsspannung (min)	220 V
Ausgangs-Betriebsspannung (max)	240 V
Output Frequenz	50/60 Hz
Anstieg der Energiemenge	600 J
Crest-Faktor	3:1
ECO-Modus	✔
Notstrom Aus (EPO)	✔
Ausgangsspannung Gesamtverzerrungsfaktor THD	2%
Geräuschpegel	55 dB
Akustische Signale	✔
Akustische Alarm-Modi	Alarm bei Batteriebetrieb, Warnung bei geringer Batterie, Überlastungsalarm

Anschlüsse und Schnittstellen	
AC-Steckertypen	C13-Koppler, C19-Koppler
Anzahl der AC-Ausgänge	3 AC-Ausgänge
USB Anschluss	✔
Serielle Schnittstelle	✔
Anzahl Ethernet-LAN-Anschlüsse (RJ-45)	1
Notaus-Steckverbinder (EPO)	✔

Akku/Batterie	
Batterielebensdauer (max.)	5 Jahr(e)
Akkuladezeit	4 h
Hot-Swap-Batterie	✔
Automatischer Batterietest	✔
Kaltstart	✔

Design	
Formfaktor *	Kompakt
Produktfarbe *	Schwarz
Displaytyp	LCD
LED-Anzeigen	✔
Internationale Schutzart (IP-Code)	IP20

Betriebsbedingungen	
Betriebstemperatur	0 - 40 °C
Temperaturbereich bei Lagerung	-15 - 45 °C
Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Luftfeuchtigkeit bei Lagerung	0 - 95%
Höhe bei Betrieb	0 - 2011 m
Höhe bei Lagerung	0 - 15240 m

Zertifikate	
Zertifizierung	CE, EN/IEC 62040-1

Lieferumfang	
Management-Karte enthalten	✔

Gewicht und Abmessungen	
Breite	440 mm
Tiefe	620 mm
Höhe	178 mm

Anschlüsse und Schnittstellen	
SmartSlot	✔
SmartConnect-Anschluss	✕

Akku/Batterie	
Akku-/Batterietechnologie	Plombierte Bleisäure (VRLA)
Akku-/Batteriespannung	96 V

Gewicht und Abmessungen	
Gewicht	51,9 kg

Verpackungsdaten	
Verpackungsbreite	590 mm
Verpackungstiefe	790 mm
Verpackungshöhe	275 mm
Paketgewicht	59 kg



0731304411826



731304411826

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date