# FSP ST 1200 Unterbrechungsfreie Stromversorgung (USV) Line-Interaktiv 1,2 kVA 720 W 4 AC-Ausgänge




**Marke :** FSP

**Artikel-Code:** PPF7200600

**Produktname :** ST 1200

FSP ST 1200. USV-Topologie: Line-Interaktiv, Ausgangskapazität: 1,2 kVA, Ausgangsleistung: 720 W. AC-Steckertypen: Typ F, Anzahl der AC-Ausgänge: 4 AC-Ausgänge, USB-Port-Typ: USB Typ-B. Batteriekapazität: 18 Ah, Akku-/Batteriespannung: 12 V, Akkuladezeit: 6,8 h. Formfaktor: Tower, Produktfarbe: Schwarz, Kühlung: Aktiv. Breite: 99 mm, Tiefe: 410 mm, Höhe: 280 mm



| Merkmale | |
|---|---|
| USV-Topologie * | Line-Interaktiv |
| Ausgangskapazität * | 1,2 kVA |
| Ausgangsleistung * | 720 W |
| Wellenform * | Sine |
| Eingangs-Betriebsspannung (min) * | 81 V |
| Eingangs-Betriebsspannung (max) * | 270 V |
| Eingangsfrequenz * | 50/60 Hz |
| Ausgangs-Betriebsspannung (min) | 110 V |
| Ausgangs-Betriebsspannung (max) | 240 V |
| Output Frequenz | 50/60 Hz |
| Regulierung der Ausgangsspannung | 5% |
| Geräuschpegel | 40 dB |
| Energieschutzeigenschaften | Batterieentladung, Überlast, Überlastschutz |
| Akustische Signale | ✔ |
| Akustische Alarm-Modi | Alarm bei Batteriebetrieb, Störung, Warnung bei geringer Batterie, Überlastungsalarm |

| Anschlüsse und Schnittstellen | |
|---|---|
| AC-Steckertypen | Typ F |
| Anzahl der AC-Ausgänge | 4 AC-Ausgänge |
| USB Anschluss | ✔ |
| Anzahl USB 2.0 Anschlüsse | 1 |
| USB-Port-Typ | USB Typ-B |

| Anschlüsse und Schnittstellen | |
|---|---|
| Anzahl Ethernet-LAN-Anschlüsse (RJ-45) | 2 |

| Akku/Batterie | |
|---|---|
| Batteriekapazität | 18 Ah |
| Akku-/Batteriespannung | 12 V |
| Anzahl Batteriezellen | 2 |
| Akkuladezeit | 6,8 h |
| Hot-Swap-Batterie | ✔ |

| Design | |
|---|---|
| Formfaktor * | Tower |
| Kühlung | Aktiv |
| Eingebauter Ventilator | ✔ |
| Produktfarbe * | Schwarz |
| Steuerung | Tasten |
| Displaytyp | LCD |

| Betriebsbedingungen | |
|---|---|
| Betriebstemperatur | 0 - 40 °C |
| Relative Luftfeuchtigkeit in Betrieb | 0 - 90% |

| Lieferumfang | |
|---|---|
| Akkus/Batterien enthalten | ✔ |

| Gewicht und Abmessungen | |
|---|---|
| Breite | 99 mm |
| Tiefe | 410 mm |
| Höhe | 280 mm |
| Gewicht | 11 kg |

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date

4713224528958

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-OCT-2026. Prints or copies of Information are only valid on the printed Publication date